



GLC 1006 is a six micron product that consistently provides the chemistry and physical characteristics you need and can rely on. It is sourced in the U.S. and produced in an ISO 9001:2008 certified facility. Packaging options include 50# bags, 2000# Super Sacks and bulk shipments.

| Typical Chemical Analysis (wt. %) |                                |      |
|-----------------------------------|--------------------------------|------|
| Calcium Carbonate                 | CaCO <sub>3</sub>              | 96   |
| Magnesium Carbonate               | MgCO <sub>3</sub>              | 2.65 |
| Aluminum Oxide                    | Al <sub>2</sub> O <sub>3</sub> | 0.20 |
| Iron Oxide                        | Fe <sub>2</sub> O <sub>3</sub> | 0.11 |
| Silicon Dioxide                   | SiO <sub>2</sub>               | <1.0 |

| Typical Physical Characteristics                         |          |
|--|----------|
| Median Particle Size                                     | 6 Micron |
| Weight % Passing 325 Mesh Screen                         | 99.7     |
| Hegman Grind Test  | 5.5      |
| Brightness: Hunter Y                                     | 74       |
| Oil Absorption   | 13       |
| Moisture – Max %   | 0.2      |
| Apparent Dry Bulk Density-Loose: lbs/ft <sup>3</sup>     | 48       |
| Apparent Dry Bulk Density-Compacted: lbs/ft <sup>3</sup> | 72       |

