



**Precautionary Statements**

Prevention

- P201- Obtain special instructions before use.
- P202- Do not handle until all safety precautions have been read and understood.
- P271- Use only outdoors or in well-ventilated area.
- P260- Do not breathe dust.
- P270- Do not eat, drink or smoke when using this product.
- P264- Wash hands thoroughly after handling
- P280- Wear eye/face protection and protective gloves.

Response

- P308 + P313 - If exposed or concerned: Get medical attention.
- P314- Get medical attention if you feel unwell.
- P302 + P352 + P362 + P363 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse.
- P304 + P340 + P312 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
- P332 + P313 - If skin irritation occurs: Get medical attention.
- P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Storage and Disposal

- P401 - Store to minimize dust generation.
- P403 - Store in a well-ventilated place
- P405 - Store locked up.
- P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical Name</b>	<b>CAS No.</b>	<b>%</b>	<b>Trade Secret</b>
Calcium carbonate	1317-65-3	17-34	*
Magnesium carbonate	546-93-0	29-86	*
Sodium sesquicarbonate	533-96-0	17-42	*
Sodium chloride	7647-14-5	0-14	*
Silica, crystalline	14808-60-7	<1	*

*\* The exact percentage (concentration) of composition has been withheld as a trade secret.*

**SECTION 4. FIRST-AID MEASURES**

**First-aid Measures**

**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if symptoms persist. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin Contact**

Flush contaminated skin with plenty of water. Get medical advice/attention if irritation persists. Remove



dusty clothing and laundry before reuse.

**Eye Contact**

Flush victim's eyes thoroughly with large quantities of water, including under eye lids. Get medical attention if irritation persists.

**Ingestion**

Rinse mouth with water. Get medical advice/attention if you feel unwell or are concerned. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

**Most Important Acute Symptoms**

Eye, skin and respiratory tract irritation.

**SECTION 5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

Not combustible. Use extinguishing agent suitable for the surrounding fire.

**Specific Hazards Arising from the Chemical**

Does not burn. Calcium carbonate decomposes at high temperature (1742 °F/950 °C) to give gaseous carbon dioxide, calcium oxide (quicklime) and magnesium oxide. Fumes of sodium oxide, chlorine and hydrogen chloride.

**Special Protective Equipment and Precautions for Fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment, and Emergency Procedures**

Avoid skin and eye contact. Avoid inhaling dust. Avoid generating airborne dust. Wear appropriate protective clothing as described in Section 8.

**Methods and Materials for Containment and Cleaning Up**

Utilize cleanup methods that minimize generating dust. Avoid dry sweeping. Keep material out of lakes, streams, ponds, and sewer drains. Dispose of via a licensed waste disposal contractor.

**SECTION 7. HANDLING AND STORAGE**

**Precautions for Safe Handling**

Use appropriate personal protective equipment (see Section 8). Avoid inhalation, skin, and eye contact. Avoid generating dust. An eye wash station should be readily available when this product is handled. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

**Conditions for Safe Storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store to minimize dust generation. Keep container tightly closed and sealed until ready for use. Containers that have



been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Keep away from moisture.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

Ingredient	CAS #	OSHA PEL	ACGIH TLV®
Calcium carbonate	1317-65-3	15 mg/m <sup>3</sup> (TWA) 5 mg/m <sup>3</sup> (TWA)(R)	NE
Magnesium carbonate	546-93-0	15 mg/m <sup>3</sup> (TWA)* 5 mg/m <sup>3</sup> (TWA)(R)*	10 mg/m <sup>3</sup> (TWA)* 3 mg/m <sup>3</sup> (TWA)(R)*
Sodium sesquicarbonate	533-96-0	NE	NE
Sodium chloride	7647-14-5	NE	NE
Silica, crystalline	14808-60-7	50 µg/m <sup>3</sup> (TWA) (R)	25 µg/m <sup>3</sup> (TWA) (R)

\* Some U.S. states with state run OSHA programs may have PELs that are different the Federal PELs listed in the table above.

### Exposure Limit Abbreviations

\*= There is no specific exposure limit for this compound. The OSHA PEL listed is for Particles Not Otherwise Regulated (PNORs). The ACGIH TLV listed is for Particles Not Otherwise Specified.

NE= None Established

ACGIH TLV= American Conference of Governmental Industrial Hygienists Threshold Limit Value ®, 2021 Edition

OSHA PEL= Occupational Health and Safety Administration Permissible Exposure Limit

TWA= Time Weighted Average

STEL= Short Term Exposure Limit

C= Ceiling Limit

mg/m<sup>3</sup>= milligram of substance per cubic meter of air

µg/m<sup>3</sup>= micrograms of substance per cubic meter of air

R= Respirable fraction of particulate sampled

I= Inhalable fraction of particulate sampled

### Engineering Controls

Use only with adequate general or local exhaust ventilation to maintain exposures to the substances above below their occupational exposure limits.

### Individual Protection Measures (Personal Protective Equipment):

#### Eye Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to dust. Wear safety glasses with side-shields if there is a risk of particles getting in eyes. In windy conditions, or if work activity generates elevated airborne dust levels, dust proof or chemical goggles may be necessary.



**Skin protection**

Appropriate skin protection measures should be selected based on the task being performed and the risks involved.

**Respiratory Protection**

Use a properly fitted, NIOSH approved particulate filter respirator if a risk assessment indicates such use is necessary or if exposures exceed the occupational exposure limits. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Grayish-white powder
<b>Odor</b>	Not applicable
<b>Odor Threshold</b>	Not applicable
<b>pH</b>	9
<b>Melting Point/Freezing Point</b>	1742 °F (950° C) (Calcium carbonate) (melting)
<b>Boiling Point/Range</b>	Not applicable
<b>Flash Point</b>	Not applicable
<b>Evaporation Rate</b>	Not applicable
<b>Flammability (solid, gas)</b>	Not applicable
<b>Upper/Lower Flammability or Explosive Limit</b>	Not applicable (upper); Not applicable (lower)
<b>Vapor Pressure</b>	Not applicable
<b>Vapor Density (air = 1)</b>	Not applicable
<b>Relative Density (water = 1)</b>	2.7
<b>Solubility</b>	Slightly soluble in water
<b>Partition Coefficient, (n-Octanol/Water (Log Kow))</b>	Not applicable
<b>Auto-ignition Temperature</b>	Not applicable
<b>Decomposition Temperature</b>	1742 °F (950 °C)
<b>Viscosity</b>	Not applicable

**SECTION 10. STABILITY AND REACTIVITY**

**Reactivity**

Not reactive under normal conditions of use.

**Chemical Stability**

Normally stable.

**Possibility of Hazardous Reactions**

Incompatible with acids, alum, ammonium salts, fluorine, magnesium, reactive fluoridated, brominated or phosphorous compounds; aluminum (may form hydrogen gas), ammonium salts, mercury, hydrogen, magnesium, reactive powdered metals; organic acid anhydrides; nitro-organic compounds; interhalogenated compounds. Reacts with acids and acidic salts to generate gaseous carbon dioxide with effervescence (bubbling) and heat. The reaction is rapid and exothermic with concentrated solutions of acids. The effervescence can create extensive foaming.

**Hazardous Decomposition Products**

None expected under conditions of normal use. Reacts with acids and acidic salts to generate gaseous carbon dioxide with effervescence (bubbling) and heat. The reaction is rapid and exothermic with



concentrated solutions of acids. The effervescence can create extensive foaming. May include but not limited to sodium oxides, chlorine gas, and hydrogen chloride.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

None of the ingredients meet the criteria of the OSHA 2012 Hazard Communication Standard to be classified as an acute toxin. The acute toxicity of the ingredients is as follows:

Chemical Name	LD50 (oral)
Calcium carbonate	6450 mg/kg (mouse)
Magnesium carbonate	> 2000 mg/kg (rat)
Sodium sesquicarbonate	> 2000 mg/kg (rat)

### Skin Corrosion/Irritation

This product is classified as a Category 2, Skin corrosion/irritation substance, under the criteria of the OSHA 2012 Hazard Communication Standard. Contact can cause dryness and irritations.

### Serious Eye Damage or Irritation

This product is classified as a Category 2B,-Serious Eye Damage/Irritation substance, under the criteria of the OSHA 2012 Hazard Communication Standard. Contact may cause can cause irritation of the eyelids, redness, and tearing.

### Respiratory or Skin Sensitization

None of the ingredients meet the criteria of the OSHA 2012 Hazard Communication Standard to be classified as respiratory or dermal sensitizers.

### Germ Cell Mutagenicity

None of the ingredients meet the criteria of the OSHA 2012 Hazard Communication Standard to be classified as a mutagenic.

### Carcinogenicity

**Silica, crystalline silica:** IARC-Group 1 (Carcinogenic to humans); NTP-K (known to be a human carcinogen); OSHA-listed.

### Reproductive Toxicity

None of the ingredients meet the criteria of the OSHA 2012 Hazard Communication Standard to be classified as reproductive toxins.

### STOT (Specific Target Organ Toxicity) - Single Exposure (SE)

This product is classified as STOT-SE, Category 3 (transient target organ effects) substance under the criteria of the OSHA 2012 Hazard Communication Standard. Symptoms of acute exposure include respiratory tract irritation.

### STOT (Specific Target Organ Toxicity) - Repeated Exposure (RE)

This product is classified as STOT-RE, Category 1 under the criteria of the OSHA 2012 Hazard Communication Standard due to the presence of crystalline silica. Prolonged inhalation of respirable crystalline silica may cause silicosis, a potentially serious lung disease. Studies have shown fibrotic lung disease in humans exposed to limestone dust, however, the health effects are thought to be associated with the presence of silica in the minerals processed or mined. Crystalline silica may also cause lung cancer, kidney damage and autoimmune disorders.

### Aspiration Hazard

No data is available, however, based on the physical form and chemistry of the product, it is not expected to



present an aspiration hazard. .

## SECTION 12. ECOLOGICAL INFORMATION

No data available for the mixture. The following information for the individual components is provided:

### Acute Aquatic Toxicity

Chemical Name	LC50 Fish
Magnesium carbonate	2120-2820 mg/L (Pimephales promelas (fathead minnow); 96-hour, fresh water; static)

### Bioaccumulation

Product is not expected to bioaccumulate.

### Mobility

Not available

## SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of according to federal, state and local regulations.

## SECTION 14. TRANSPORT INFORMATION

### U.S. Department of Transportation (DOT)

Product is not regulated

### International Maritime Dangerous Goods (IMDG)

Product is not regulated

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Product is not regulated

### International Civil Aviation Org./ International Air Transport Assoc. (ICAO/IATA)

Product is not regulated

## SECTION 15. REGULATORY INFORMATION

### CERCLA Hazardous Substances

Not listed

### SARA Toxic Chemical (40 CFR 372.65)

Not listed

### SARA Section 302 Extremely Hazardous Substances (40 CFR 355)

Not listed

### SARA 311/312

Not listed



**SARA Section 313 Toxic Chemicals reporting requirements**  
None

**Threshold planning quantity (TPQ)**  
Not listed

**RCRA Hazardous Waste Classification (40 CFR 261)**  
Not Classified

**EPA Toxic Substances Control Act (TSCA) Status:**  
All of the components of this product are listed on the TSCA

**California Proposition 65 Compliance**  
This product contains or produces chemicals (crystalline silica) known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code 25248.5 et seq.)"

## **SECTION 16. OTHER INFORMATION**

DATE: August 25, 2021

This SDS is intended to be used as a guide to the appropriate handling, storage, and use of this product by an adequately trained person. GLC Minerals, LLC is not responsible for the misuse, mishandling or improper storage of this material by the user. GLC MINERALS, LLC NEITHER MAKES, NOR OFFERS NOR SHALL BE HELD LIABLE FOR ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WITH RESECT TO THE USE OF THE INFORMATION PROVIDED.